

Nikon

NIKON SPEEDLIGHTS

SB-30 Speedlight

Compact, Lightweight and Versatile TTL Speedlight



- New Compact Design: Compact design (only 3.2 oz) allows for unobtrusive on camera flash
- New Downward Tilt: Promotes on camera close ups and easy portability
- New 17mm Wide Flash Adapter: Wide flash adapter for use with lenses as wide as 104° angle of view
- ┌ New Built-in Wireless Flash: Operates as a wireless speedlight for multiple flash photography up to 23 feet, Auto or Manual to 131 feet
- ┌ New Built-in Infrared Remote Commander: Allows for triggering of off camera speedlights during wireless multiple flash operations
- New Safety Lock System: Locking system assures positive contact between SB-30 and SLR in use
- Guide Number: 52 at ISO100 with 28mm in feet
- New Multi Platform Capability: Operates with Nikon 35mm and Digital SLR as well as select Coolpix products

SB-30 Speedlight

Two key concepts have driven Nikon flash innovations: automation and integration. The automation is found in Nikon's Matrix Balanced Fill-Flash, 3D Multi-Sensor Balanced Fill-Flash and multiple flash technologies. Integration is the seamless blending of flash capability with Nikon cameras' exposure systems. With Nikon Speedlights, you can capture the scene you see and the one you create in your mind's eye.

Speedlight Specifications:

Type of Speedlight:	Automatic Insulated Gate Bipolar (IGBT) and series circuitry
Guide Number:	52 at 28mm setting with ISO 100 in feet
Angle of Coverage:	Covers 28mm without Wide Flash adapter Covers 17mm with Wide Flash adapter
Power Switch:	Three provided: Off/On/Standby (automatically turns off after approx 40 seconds if flash is not in use)
Recycle Time and Number of Flashes:	Minimum recycle time approx. 4 seconds when fired at M1/1 output using a fresh battery
No. of Flashes:	Approx. 250 times at M1/1 using a fresh battery
Mode Selector Dial:	TTL Auto flash, Non-TTL Auto flash (4 steps), Manual Mode (3 steps) and Wireless flash (A or M only)
Ready Light:	Light up when SB-30 is recycled and ready to fire
Power Source:	One 3V lithium battery (CR-123A or DL-123A)
Accessories:	Soft Case SS-30 included
IR Panel:	Provided
Wide Panel:	Provided
Dimensions (W x H x D):	Approx. 2.3 X 3.3 X 1.4 inches
Weight:	Approx. 3.2 oz.
Product Number:	4718 NCP

For more complete specifications and compatibility information, refer to the SB-30 Speedlight instruction manual. Specifications and design are subject to change without any notice or obligation on the part of the manufacturer. 2/02

© 2002 Nikon Inc.

